

CMT 2000



Specifications

Features

- Convergence and Disparity Control
- Parallel/Alternate (Parallel Movement)
- Two simultaneous power-adjustable camera disparity range, -82mm ~ 352mm
- LANC Controller for controlling two cameras (Simultaneous Camera Control LANC REC./STOP, ZOOM in/out, POWER)
- Fine adjustment of convergence with manual controlled left and right movement knob
- Horizontal and optical axis micro control

Size

- 503 * 168 * 124mm

Camera Interval

- Camera Disparity Range: 84 ~ 352mm

Power

- DC 12V 9,600mA

Tilt /Rotary Angle

- Gonio Stage (tilt range) $\pm 10^\circ$
- Right Left Angle 30°

Weight

- 5.8kg

Material/Surface Treatment/Color

- Aluminum/Anodizing/Black

Accessories

- Power Adaptor-1ea, Power Cable-1ea,
- 3/8 inch bush Adaptor 2ea, 1/4 inch screw 2ea, Quick Shoe 2ea.
- Durable Travel Range

Options

- LANC Cable, Wired External LANC CONTROLLER

Camera Support

[Lanc Control Support]

- Sony DCR-HC9

[Normal Camera]

- 5kg within HDV or HD Camera, RED, EX3